



## Technical Specifications PodiumCafé

This is only a summary of our technical facilities, and is subject to change.

We run a 'Fixed Rig' policy. Please call or mail for any further technical background, or general information.

## Stage dimensions PodiumCafé:

Depth: 3.00M

Width: 5.00M

Clearance: 3.00M

Height: 0.60M

## Sound

*Max legal sound limit: 103 dBa over 15 min*

## Mixing console:

Digital - Midas PRO2c (with DL251, 48 channel stagebox) (own I/O) (Firmware G3.4.6)

## P.A.:

- 2 -L-Acoustics 115Xt HIQ 15"
- 1 -L-Acoustics LA-8 4 channel amplifier
- 2 - 18" subwoofer
- 2 - Labgruppen 2 channel amplifier Lab 1000

## Stage

### Monitoring:

- 4 -L-Acoustics 115Xt HIQ 15" floormonitor
- 2 -L-Acoustics LA-8 4 channel amplifier

### Drum fill:

- 1 -JBL VRX915M drum fill top 15"+ 1"
- 1 -JBL VRX915S drum fill sub 15"
- 1 -Labgruppen Q2400 (sub)
- 1 -DBX driverack 260



**Microphones:**

Sufficient various mics

**Stands:**

Sufficient various stands

**Auxiliary Equipment:**

- 4 - BSS AR133 DI Box (active)
- 1 - 24 send 4 return stagebox and Multicore to F.O.H. (installed stage Left)

**Cable:**

Sufficient XLR cable

**Lighting**

**Lighting control:**

- 1 - Avolites Quartz v15

**Moving light:**

- 6 - Martin Rush MH2

**Lanterns:**

- 13 -Parcan - LED
- 6 -Parcans – Conventional (front)
- 4 -Parcans – Conventional (side)

**Visuals**

**Projection:**

- 1 \* Optoma W501 (5,000 Lumens)
- 1 \* Projection screen (4:3) 300\*225 (fixed position stage back)



## Electricity

### Power:

4 \* 16A 220V Ceeform outlet Stage. (Situating Stage Left(1), Back(1) and Right(2))

1 \* 16A 220V Ceeform outlet FOH. (Situating FOH connection Cabinet)

### Electrical safety:

All incoming electrical equipment should be safe, well maintained and have been portable appliance tested. Although documentation will not strictly be required, evidence of testing should be available. In-house staff will not allow potentially unsafe equipment to be used or connected to the electrical systems.

**The Boerderij will assume no responsibility, if the incoming company cannot comply with these requests.**